

iGuard

IP/Network Camera

iGuard™ features an embedded multi-port WEB/network video server as small as a deck of cards, but functions as powerful as dedicated computer-based video streaming system. iGuard™ is the only IP camera solution on the market today that has a built-in expansion port to which a large selection of USB cameras and add-on's can be attached.



iGuard™ IP-390E



iGuard™ IP-390E features:

- ✍ 180Mhz 32Bit RISC Processor (ARM9) /w 16MB
- ✍ 802.11A/B WiFi
- ✍ 640x480 High Resolution color CMOS Sensor
- ✍ Up to 30 fps and 30 simultaneous viewers
- ✍ 36 LED with up to 30ft illumination
- ✍ Weather resistant alloy housing
- ✍ Free PC-Based Multichannel Recording software

Optional Add-on Cameras



Clip-on IR USB Camera
Model No. iCam-01



Add-on USB Camera
Model No. iCam-05



Pan/Tilt/Zoom USB Camera
Model No. iCam-03



Bullet USB Camera
Model No. iCam-04



PRO USB Camera
Model No. iCam-02

More iGuard IP Cameras



Mini IP Camera
Model No. IP-250E



Pro IP Camera
Model No. IP 310E



PRO Box IP Camera
Model No. IP-220E



Day/Night Outdoor IP Camera
Model No. IP-290E



IR Dome IP Camera
Model No. IP-270E

iGuard

Web Based Remote Surveillance Solutions

Features

■ iGuard 301S Embedded Network Video Server

- Built-in USB host for additional USB devices
- Built-in Pan/Tilt Controllers
- Supports add-on cameras with resolution up to 1024 x 768
- Audio Option with audio enabled add-on camera
- WiFi Ready with USB wireless dongle
- up to 30 simultaneous remote viewers
- Configure up to 8 user accounts with different access levels (administrator, operator and viewer)
- Configure up to 4 Permit Hours per user account
- Adjustable FPS allocation to each user account
- Support PPPoE and DDNS
- MJPEG Streaming/MPEG4 Recording
- Built-in RS232 ADIO port supports wireless sensor gateway
- Web-based remote access using any Java- enabled web browser 10/100Mbps fast Ethernet connection
- Motion Detection (continuous or scheduled)
- Motion Tracking with compatible PT camera
- Scheduled Recording
- Email Notification of Events, Motion Detects and Scheduled Image Recordings
- Option to store images to a FTP server
- Display Current Connections (Viewer IP, status, active camera, login time, total data TX, etc.)
- Block/Black-list up to 256 IP addresses
- Detailed Event Log with ability to sort and save
- Frame Rate: Up to 30 at 320x240

■ Camera

- VIMICRO ZC0301Plus image processor
- Color CMOS VGA Sensor with 350,000 pixels
- USB 2.0, backwards compatible to USB 1.1
- Adjustable Focus Lens (5cm to infinity)
- Minimum Illumination: 2.5lux@f1.4
- Visual Angle: 62 degree horizontal
- Image Control: Exposure Compensation, Color/Mono Switch, Light Source Selection (Anti-Flick)
- Pan: 352, Tilt: 90, Digital Zoom

■ Bundled Software: iGuardView Network DVR

Applications



Video Conference



Home Security



Remote Office Management



Inventory Loss Prevention

MICON Technology, Inc.

<u>China</u>	<u>USA</u>
5F A Building	13608 Merriman Road
ShuiTou Industrial Estate	Livonia, MI 48150, USA
YouSong, LongHua, BaoAn,	Tel: 734-261-3828
ShenZhen, China 518109	Fax: 734-261-4139
www.lyd.cc	www.micon.com